

TX-NR509 5.1-CHANNEL NETWORK A/V RECEIVER







Audyssey











































Affordable Home Theater Centerpiece with Audio Network Capability

New at the entry level, the networking ability of the TX-NR509 takes you one step closer to fully integrated home entertainment. Audio files on your computer and streaming internet radio can both now be played through your main system, with fidelity far beyond what you're used to on a PC. When it comes to setting up the TX-NR509, Audyssey 2EQ® works to adapt the soundstage to the unique dimensions of your room. On-the-fly adjustments to audio and video settings are simple, thanks to the user-friendly overlaid on-screen display. Additional system control is provided by Onkyo's Remote App, which lets you use your iPod/iPhone as a remote controller. The receiver's four advanced HDMI® inputs handle stunning high-definition audio from Dolby and DTS, as well as dynamic new 3D video. Further connectivity highlights include a new front-panel USB port that offers a clean digital link for both iPod/iPhone and USB storage devices, and Zone 2 line-outs that let you send a stereo audio signal to a second room equipped with an amp and speakers. All in all, the TX-NR509 offers a superb feature set for the valueconscious home theater fan.

ADVANCED FEATURES

- HDMI® Support for 3D, Audio Return Channel, Deep Color™, x.v.Color™, LipSync, Dolby® TrueHD, DTS-HD Master Audio™, DVD-Audio, Super Audio CD, Multichannel PCM, and CEC
- Direct Digital Connection of iPod®/iPhone® via Front-Panel USB Port
- Supports Onkyo Remote App for Control of A/V Receiver via iPod/iPhone*1 (Early 2011)
- Dolby® TrueHD and DTS-HD Master Audio Decoding • Overlaid On-Screen Display (OSD) via HDMI
- Audyssey 2EQ® for Room Acoustic Correction
- Playback of Audio Files Through Local Network (MP3, WMA, WMA Lossless, FLAC, WAV, Ogg Vorbis, AAC, LPCM)
- Internet Radio and Music Streaming Service Connectivity (vTuner, SIRIUS XM Internet Radio®, Mediafly, Pandora®, Slacker™, Rhapsody®, Napster)*²
- Certified with Windows® 7 and DLNA Version 1.5
- Firmware Updates via Ethernet and USB
- Zone 2 Line-Out for Distributed Audio Playback in Another Room
- *I Compatible iPod/iPhone models: iPod touch 3rd gener iPhone 3GS or later. (All models require iOS 4.2 or later.) *2 Availability of services depends on region.

AMPLIFIER FEATURES

• 80 Watts per Channel at 8 Ohms, 20 Hz-20 kHz, 0.7%, 2 Channels Driven, FTC;

- 110 Watts per Channel at 6 Ohms, 1 kHz, 0.9%, 2 Channels Driven, FTC
- H.C.P.S. (High Current Power Supply) Massive High Power Transformer
- Optimum Gain Volume Circuitry
- PLL (Phase Locked Loop) Jitter-Cleaning Circuit Technology for S/PDIF Audio

PROCESSING FEATURES

- TI Burr-Brown 192 kHz/24-Bit DACs for All Channels
- · Advanced 32-Bit Processing DSP Chip
- 4 DSP Modes for Gaming: Rock, Sports, Action, and RPG
- Advanced Music Optimizer for Compressed Digital
- Mass Storage Class USB Memory Playback Capability
- Theater-Dimensional Virtual Surround Function • CinemaFILTER"
- Direct Mode
- Double Bass Function
- Non-Scaling Configuration
- A-Form Listening Mode Memory

CONNECTION FEATURES

- 4 HDMI Inputs and I Output
- Universal Port for Onkyo Dock for iPod/iPhone (UP-AI) or HD Radio™ Tuner (UP-HTI)

- HDTV-Capable (720p/1080i) Component Video Switching (2 Inputs and 1 Output)
- 5 Composite Video Inputs (I Front/4 Rear) and 2 Outputs • 4 Digital Audio Inputs (2 Optical and 2 Coaxial)
- 6 Analog Audio Inputs (I Front/5 Rear) and I Output
- Subwoofer and Surround Back Pre Outs
- · Color-Coded, Banana Plug-Compatible
- Headphone lack

OTHER FEATURES

- Audyssey Dynamic EQ® for Loudness Correction
- Audyssey Dynamic Volume® to Maintain Optimal Listening Level and Dynamic Range
- Crossover Adjustment (40/50/60/70/80/90/100/120/ 150/200 Hz)
- A/V Sync Control (Up to 400 ms at 48 kHz)
- Tone Control (Bass/Treble) for Front L/R Channels
- 3-Mode Display Dimmer (Normal/Dim/Dimmer)
- 40 FM/AM Random Presets
- RIHD (Remote Interactive over HDMI) for System Control
- Full-Function RI (Remote Interactive) Remote Control



TX-NR509 5.1-CHANNEL NETWORK A/V RECEIVER

HDMI® Support for 3D Video and Audio Return Channel

The four HDMI inputs on the TX-NR509 let you simultaneously connect high-def sources such as a Blu-ray player, a gaming console, and a cable/satellite tuner, A single output then sends a pristine signal to your connected highresolution display. The HDMI implementation on this receiver supports both 3D video and an Audio Return Channel, along with numerous high-resolution formats. 3D video brings exciting possibilities to home entertainment, with movie, game, and broadcast content on the increase and 3D-compatible TVs now on the market. Meanwhile, the Audio Return Channel allows audio content received directly by your HDTV's tuner to be sent "upstream" via HDMI to your A/V receiver, without the need for a separate S/PDIF audio cable.

Network Capability Delivers Internet Radio and Network Audio Streaming via Ethernet

As one of Onkyo's new breed of receivers that can link directly to the internet or to your home PC via a local network, the TX-NR509 takes streaming audio and internet radio to a whole new level. MP3, WMA, WMA Lossless, FLAC, WAV, Ogg Vorbis, AAC, and LPCM audio files can now be played back through your main system with unprecedented power and fidelity. The TX-NR509 also brings to life a huge array of internet radio channels from vTuner: SIRIUS XM Internet Radio®, Mediafly, Pandora®, and Slacker™, plus on-demand music streaming from Napster and Rhapsody*. As well as being compatible with earlier platforms, the receiver is compatible with Microsoft's Windows® 7 platform, which includes the DLNA 1.5-specified "Play To" media-streaming feature. The TX-NR509's internet connectivity has the added benefit of making firmware updates simpler than ever. *Availability of services depends on region.

Direct Digital Connection of iPod®/iPhone® via Front-Panel USB Port

The TX-NR509's front-panel USB port lets you access MP3 WMA, WMA Lossless, FLAC, WAV, Ogg Vorbis, and AAC audio files stored on a USB flash drive or iPod/iPhone. As the audio signals are transported in digital form, rather than analog, there is much less chance for signal degradation. End result: your music sounds cleaner and more faithful to the original. A further benefit of the USB input is that it lets you use the system's remote controller to play back audio files on the connected device.

Onkyo Remote App for iPod/iPhone*

Available as a free download, this app lets you use your iPod touch or iPhone as a remote controller to control a range of functions on the TX-NR509. As well as letting you select internet radio stations, it also lets you select streaming audio input from a DLNA-compatible server. The Remote App also enables you to perform basic playback operations and control the receiver's volume with an interface that uses the iPod/iPhone's built-in accelerometer *Compatible iPodliPhone models: iPod touch 3rd generation or later; iPhone 3GS or later. (All models require iOS 4.2 or later.)

Convenient Overlaid On-Screen Display via HDMI

Changing your A/V receiver's settings is now more seamless than ever, thanks to the TX-NR509's overlaid On-Screen Display (OSD) feature. On-screen set-up menus appear overlaid on the video image you're watching. This means you can adjust the settings immediately, without having to switch back and forth from a blank screen background.

Universal Port for Single-Cable Connection of Optional Onkyo Dock for iPod®/iPhone® or HD Radio[™] Tuner

A proprietary Universal Port located on the rear side of the TX-NR509 lets you connect an optional UP-A1 Dock for iPod/iPhone or UP-HT1 HD Radio Tuner. A key advantage of the Universal Port is that it accepts video and audio signals through the same cable that sends a power supply from the receiver to the devices. Net result: more connectivity, less cable clutter

Advanced Music Optimizer to Enhance Compressed Digital Music Files

While MP3 or AAC files may sound fine through the headphones of your portable digital player, the limitations of these files can be exposed when played back through a quality home entertainment system. This is because a significant amount of high-frequency bit information is lost during the file-compression process. To counter this, Onkyo has designed the Advanced Music Optimizer to compensate for lost bit information and improve the quality of compressed audio signals. This results in a clearer and more expansive sound. Also included in this technology is a loudness correction feature that further improves the audio character of compressed files.

Playback of Different Audio Sources in Two Different Zones

Zone 2 line-outs on the TX-NR509 allow you to enjoy surround-sound entertainment in the main room, while playing back a different stereo source in a second zone equipped with an amplifier and a pair of speakers.

A Suite of Audyssey Technologies for the Ideal Listening Environment

The TX-NR509 comes equipped with three soundenhancing Audyssey technologies.

(I) Audyssey 2EQ® tailors multi-channel audio for your home eater speaker set-up by measuring three room positions and applying a resolution filter to the satellite speakers to correct for

(2) Audyssey Dynamic EQ® maintains a consistent bass response, tonal balance, and surround-sound effect at different volume levels so you can enjoy the natural dynamics of your content regardless of

(3) Audyssey Dynamic Volume® automatically compensates for volume fluctuations in different audio content—for example, during commercial breaks—while optimizing the dynamic range

SPECIFICATIONS Amplifier Section

Ampinici Section	
Power Output	
Front L/R	80 W/Ch (8 ohms, 20 Hz-20 kHz, 0.7%,
	2 channels driven, FTC);
	110 W/Ch (6 ohms, 1 kHz, 0.9%,
	2 channels driven, FTC)
Center	80 W (8 ohms, 20 Hz-20 kHz, 0.7%,
	2 channels driven, FTC);
	110 W (6 ohms, 1 kHz, 0.9%,
	2 channels driven, FTC)
Surround L/R	80 W/Ch (8 ohms, 20 Hz-20 kHz, 0.7%,
	2 channels driven, FTC);
	110 W/Ch (6 ohms, 1 kHz, 0.9%,
	2 channels driven, FTC)
Dynamic Power	180 W (3 ohms, Front)
	160 W (4 ohms, Front)
	100 W (8 ohms, Front)
THD+N (Total Harmor	nic Distortion + Noise)
,	0.08% (20 Hz-20 kHz, Half power)
	/ O / E

Damping Factor 60 (Front, I kHz, 8 ohms) Input Sensitivity and Impedance
200 mV/47 k-ohms (Line)

Rated RCA Output Level and Impedance
200 mV/2.2 k-ohms (Rec out)

Maximum RCA Output Level and Impedance
2.0 V/2.2 k-ohms (Rec out) Frequency Response 20 Hz-50 kHz/+1 dB, -3 dB (DSP bypass) Tone Control +10 dB. 20 kHz (Treble) Signal-to-Noise Ratio 100 dB (Line, IHF-A) Speaker Impedance

6 ohms-16 ohms

Video Section

Input Sensitivity/Output Level and Impedance I.O Vp—p/75 ohms (Component Y)

0.7 Vp—p/75 ohms (Component PB/CB, PR/CR) Video 1.0 Vp-p/75 ohms (Composite)

Component Video Frequency Response

5 Hz-100 MHz/0 dB, -3 dB

Tuner Section	
Tuning Frequency Range	
FM	87.5 MHz-107.9 MHz
AM	530 kHz-1,710 kHz
FM/AM Preset Memory	40 stations
General	
Power Supply	AC 120 V~, 60 Hz
Power Consumption	3.9 A
Dimensions (W x H x D)	17 1/8" × 6 13/16" × 12 15/16"
	(435 × 173.5 × 328 mm)
Weight	18.7 lbs. (85 kg)

CARTON	
Dimensions (W x H x D)	22 ⁷ /16" × 11 ¹¹ /16" × 16 ⁵ /8"
	(570 x 297 x 423 mm)
Weight	25.4 lbs. (11.5 kg)

UPC CODE

Supplied Accessories

- Indoor FM antenna AM loop antenna Speaker cable labels Speaker set-up microphone Instruction manual Quick set-up guide Remote controller AA (R6) batteries x 2



Due to a policy of continuous product improvement, Onlyo reserves the right to change specifications and appearance without notice. Manufactured under license from Dolby Laboratories. Dolby, Pro Logic, and the double-D symbol are trademarks of DTS, DTS-HD, and the Symbol are registered trademarks and the DTS logics are trademarks of DTS, Inc. Manufactured under icense from Audyssey Laboratories, Inc. LUS and foreign patients pending, Audyssey ZEQ, Audyssey Dynamic EQ, and Audyssey Dynamic Volume are registered trademarks of Audyssey Laboratories, Inc. HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of Apple inc., registered in the US, and other countries. Phone, iPod, Pod classic, iPod nano, Pod shuffle, and Pod touch are trademarks of Apple inc., registered in the US, and other countries. Phade for iPhone "mean that an electronic accessory has been designed to connect specifically to iPod or iPhone, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Please note that the use of this accessory with iPod or iPhone may affect wireless performance. xv.Color is a trademark of Sony Corporation. Windows 7 and all related marks and logics are trademarks or registered trademarks of Microsoft Corporation in the United States. SIRUS, XM and all related marks and logics are trademarks are the property of their respective holders.

