

SKS-HT594 5.1.2-Channel Home Theater Speaker System



BLACK



Experience the Magic of Next-Gen Cinema Sound

This six-piece speaker package reproduces everything from multidimensional Dolby Atmos® soundtracks to MP3s streamed from your phone with utmost precision. Two-way front speakers feature large paper-cone woofers and balanced-dome tweeters to articulate wide-spectrum audio with timing, clarity, and scale. They include an upfiring driver housed in a compartment in the top of the cabinet which bounces “sound objects” contained in Dolby Atmos and DTS:X™ soundtracks off the ceiling and into the audience, convincingly replicating sounds that originate from overhead. Joining two compact, wall-mountable surround-sound speakers and the dual-drive 2-Way center speaker is a powerful 10-inch subwoofer delivering up to 120 W of wall-shaking bass. The handsome SKS-HT594 package is the most convenient way to get immersed in next-generation cinema sound magic.

SKF-2800 Dolby Atmos®-Enabled Integrated Front & Height Speakers

- 5" (12 cm) Cone Woofer
- 1" (2.5 cm) Balanced-Dome Tweeter
- 3 1/4" (8 cm) Cone (Separately Powered By Height Channel)
- Max. Input Power: 130 W
- Wall-Mounting Capability

SKC-594 2-Way Bass Reflex Center Speaker

- 3 1/4" (8 cm) Cone Woofer x 2
- 1" (2.5 cm) Balanced-Dome Tweeter
- Max. Input Power: 130 W
- Wall-Mounting Capability

SKR-594

Full-Range Acoustic-Suspension Surround Speakers

- 3 1/4" (8 cm) Cone
- Max. Input Power: 130 W
- Wall-Mounting Capability

SKW-593 Bass Reflex Powered Subwoofer

- 10" (25 cm) Cone
- Rated Output Power: 120 W (Minimum Continuous Power, 4 Ohms, 100 Hz, 1%, FTC)
- Energy-Saving High Power Amplifier
- Down-Firing Design

SPECIFICATIONS

SPEAKER SYSTEM

Speaker Type	2-Way, Bass Reflex
Front	Full-Range, Acoustic-Suspension
Height	2-Way, Bass Reflex
Center	Full-Range, Acoustic-Suspension
Surround	Bass Reflex, Powered
Subwoofer	
Drivers	
Front	5" (12 cm) Cone Woofer
Height	1" (2.5 cm) Balanced-Dome Tweeter
Center	3 1/4" (8 cm) Cone
Surround	3 1/4" (8 cm) Cone Woofer x 2
Subwoofer	1" (2.5 cm) Balanced-Dome Tweeter
	3 1/4" (8 cm) Cone
	10" (25 cm) Cone
Frequency Response	
Front	55 Hz–50 kHz
Height	80 Hz–20 kHz
Center	65 Hz–50 kHz
Surround	80 Hz–20 kHz
Subwoofer	25 Hz–150 Hz
Output Sound Pressure Level	
Front	83 dB/W/m
Height	81 dB/W/m
Center	86 dB/W/m
Surround	81 dB/W/m
Max. Input Power	
Front/Height/Center/Surround	130 W
Rated Output Power	
Subwoofer	120 W (Minimum Continuous Power, 4 Ohms, 100 Hz, 1%, FTC)

Nominal Impedance	Front/Height/Center/Surround 6 Ohms
Input Sensitivity/Impedance	Subwoofer 540 mV/20 k-ohms
General	
Dimensions (W x H x D)	
Front/Height	6 1/8" x 18 1/8" x 7 3/16" (155 x 467 x 183 mm)
Center	16 1/8" x 4 1/2" x 4 3/4" (409 x 115 x 121 mm)
Surround	4 1/2" x 9 1/16" x 3 3/4" (115 x 230 x 96 mm)
Subwoofer	12 1/2" x 18 1/4" x 15 1/16" (317.5 x 463 x 398 mm)
Weight	
Front/Height	8.2 lbs. (3.7 kg)
Center	4.9 lbs. (2.2 kg)
Surround	2.2 lbs. (1.0 kg)
Subwoofer	21.2 lbs. (9.6 kg)
CARTON	
Dimensions (W x H x D)	30 3/8" x 23" x 20 1/4" (772 x 584 x 514 mm)
Weight	57.3 lbs. (26.0 kg)
UPC CODE	
(B)	751398012402
Supplied Accessories	
• Color-coded speaker cables • Subwoofer cable	

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. Manufactured under license from Dolby Laboratories. Dolby Atmos and the double-D symbol are trademarks of Dolby Laboratories. Manufactured under license from DTS Licensing Limited. For DTS patents, see <http://patents.dts.com>. DTS, DTS-HD, the Symbol, & DTS and the Symbol together are registered trademarks, and DTS:X is a trademark of DTS, Inc. © DTS, Inc. All Rights Reserved. All other trademarks and registered trademarks are the property of their respective holders.